



On-grid Three Phase Inverter

Suntrio Plus 4K/5K/6K/8K/10K



Safe and Reliable

- Natural convection for longer life
- IP65 protection

Flexible and Efficient

- MPPT efficiency 99.9%
- Super wide input voltage range

Smart and Easy to Use

- RS485/Ethernet/ Wi-Fi/GPRS modules
- Remote Maintenance

Convenient Installation

- Transformerless, smaller and lighter
- DC&AC quick connector

Technical Data

Suntrio Plus 4K/5K/6K/8K/10K

Type	Suntrio Plus 4K	Suntrio Plus 5K	Suntrio Plus 6K	Suntrio Plus 8K	Suntrio Plus 10K
Input (DC)					
Max. DC Power [W]	4840	6050	7260	9680	12000
Max. DC Voltage [V]			1000		
MPPT Voltage Range [V]			160-900		
Nominal DC Voltage [V]			600		
Start Voltage [V]			180		
Min. DC Voltage [V]			150		
Max. DC Input Current PV1 / PV2 [A]		11/11		22/11	
Number of MPPT			2		
Number of DC Connection Sets per MPPT		1/1		2/1	
DC Switch			Integrated		
Output (AC)					
Rated AC Power [W] (@230V,50Hz)	4000	5000	6000	8000	10000
Max. AC Power [VA]	4400	5500	6600	8800	10000
Rated AC Current [A]	5.8	7.2	8.7	11.6	14.5
Max. AC Current [A]	6.4	8.1	9.7	12.9	15.9
Nominal AC Voltage / Range		3L/N/PE, 220/380V, 230/400V, 240/415V; 180V-280V/312V-485V			
Grid frequency / Range		50Hz, 60Hz / 44Hz-55Hz, 54-65Hz			
Power factor, Adjustable [cos φ]		0.8 leading~0.8 lagging			
Total Harmonic Distortion [THDi]		< 3% (at nominal power)			
Feed-in		3L+N+PE			
Efficiency					
Max. Efficiency	97.8%	97.8%	97.8%	98.0%	98.0%
Euro Efficiency (at 600Vdc)	97.0%	97.2%	97.4%	97.5%	97.6%
MPPT Accuracy			>99.9%		
Protection					
Internal Over-voltage Protection			Integrated		
DC Insulation Monitoring			Integrated		
DCI / GFCI / Grid Monitoring			Integrated		
AC Short Circuit Current Protection			Integrated		
Thermal Protection			Integrated		
Anti-island protection monitoring			AFD		
Interface					
DC Connection			MC4/H4		
AC Connection			Plug-in connector		
LCD Display		3.5 inch Graphic LCD Display, Backlight, Inverter Parameter and Data Display			
Display Language			English		
Datalogger & Communication		1*RS485 +1*RS232 ; Wi-Fi/GPRS/Ethernet (Optional)			
General Data					
Topology			Transformerless		
Consumption at Night [W]			<0.6		
Consumption at Standby [W]			<10		
Operating Temperature Range		-25°C to +60°C (45°C to 60°C with derating)			
Cooling Method		Natural Convection			
Ambient Humidity		0% to 100% Non-condensing			
Altitude		Up to 2000m (without power derating)			
Noise [dBA]		<29			
Ingress Protection		IP65 (Indoor & Outdoor Installation)			
Mounting		Rear Panel			
Dimensions (H*W*D) [mm]		530*355*190		530*355*200	
Net Weight [kg]		20.5		23.0	
Standard Warranty [Year]		5 (Standard) / 10 / 15 / 20 / 25 (Optional)			
Certificates	IEC/EN62109-1/2, IEC61683, IEC60068-2, IEC62116, IEC61727, EN61000-6-2/3,C10/11,VDE0126-1-1/A1, VDE-AR-N 4105, CQC NB/T 32004, G83/2,EN50438,CEI-021				

Remarks: The above parameters might be slightly modified according to different grid codes